

**FAST.
EXACT.
EFFICIENT.** ✓



PATENTED SPI PIPE CLAMP SCREW ANCHOR


So far, there has been no convincing solution for the subsequent attachment of pipe clamps, signs, lights, etc. on thermally insulated facades. Now: Grömo offers a pipe clamp screw anchor with M10 threads which optimally inserts into the thermal insulation. The SPI pipe clamp anchor screw is completely made of plastic. So, no thermal bridges are formed and the thermal insulation works. The rosette seals the hole perfectly and makes for a beautiful finish.

Advantages for the construction site:

- Stable, highly durable, stainless steel bracket
- Three lengths, suitable for almost any wall material
- Completely made of plastic, metal pin with screw slot to attach the pipe clamp
- Quick and easy installation after facade completion
- Significant time savings compared with improvisations and self-made constructions
- No costly repairs of poorly mounted pipes

Benefits for the client:

- Patented screw anchor range
- Completely made of plastic, therefore no thermal bridges
- Protection against moisture and rain through dense, shapely rosette finish
- No transmission of structure-borne and dripping noises
- For all full insulation facades of 80 to 220 mm



Mounting

- 1 Simply drill. Drill in the hollow concrete block without percussion drilling, tappet in gas and aerated concrete. See too Figure 1 on the back. Use green silicone hose for use in aerated concrete.
- 2 Select screw anchor length depending on the thickness of the ETICS system, twist out metal pin and hammer the screw anchors into the wall until the rosette sits properly.
- 3 The rosette with a sealing ring ensures an elegant, flush finish and protects the facade from rain and moisture.
- 4 Turn metal pin again and fasten clamp – done.

Types and Technical Data

Item No.	Spezification	Use
50236	Plastic screw anchor rod 130 mm diameter 14 mm with washer and threaded pin M 10	For mounting directly to the wall without ETICS
50237	Plastic screw anchor rod 260 mm diameter 14 mm with washer an threaded pin M 10 (ETICS)	For direct mounting in ETICS up to 160 mm insulation thickness
50238	Plastic screw anchor rod 330 mm diameter 14 mm with washer an threaded pin M 10 (ETICS)	For direct mounting in ETICS up to 220 mm insulation thickness